



# NET'GUARD® ULTRA 4 IN 1



## CONCENTRATED SUPER CLEANER STRIPS ALL HEAVILY SOILED SURFACES

- ✓ **4-IN-1: DEGREASES, CLEANS, POWERFULL AND HYPER-ACTIVE ACTION**
- ✓ **DISSOLVES STAINS AND MARKS**

- ✓ **MULTI-FUNCTIONAL: FLOORS, FACADES AND ALL MATERIALS**
- ✓ **ECOLABEL FORMULA CERTIFIED FOR CONTACT WITH FOOD**
- ✓ **EXTERIOR AND INTERIOR**

### ADVANTAGES AND CHARACTERISTICS

- Powerful, rapid-action cleaner.
- Removes the most persistent marks and greasy stains (mineral oils, greases, tyre marks, etc.).
- Ready to use, can be applied to all mineral substrates.
- Non-corrosive, non-irritant and without neutralising after rinsing.
- Complies with the regulation of 19/12/13 on cleaning of equipment that may come into contact with food.

### USE

Net'Guard® Ultra 4 in 1 can be used inside and outside on floors, facades and walls. Ideal for cleaning all types of materials of concrete, natural or reconstituted stone, terracotta, tiles, stoneware, marble, paving stones, asphalt, composite wood etc. It does not alter plastic or rubber.

### CONTAINERS

5 and 20 litres.

### ENVIRONMENT

#### Respects the environment and is ecological:

- Water-based product, without soda and potash.
- Non-hazardous and non-toxic.
- The surface agents contained in this formula are biodegradable to more than 60%\* in 28 days.
- Complies with the regulation of 19/12/13 on cleaning of equipment that may come into contact with food.

### APPLICATION

- Net'Guard® Ultra 4 in 1 is a concentrated, ready-to-use product.
- Always test on the substrate before application.
- Apply the product liberally to the substrate to be treated.
- Allow it to work for 15 to 30 minutes depending on the soiling to be removed.
- Brushing with a standard broom may improve the effectiveness of the product.
- Do not allow the product to dry before rinsing with water.
- Rinse the entire surface with a pressure washer with hot or cold water to increase the effect.
- It is not necessary to neutralise the treated surface.

## APPLICATION TOOLS

- Apply with a lower pressure spray.

## PREVENTION

- To avoid any new soiling after cleaning and drying the substrate, it is recommended that you apply a preventive treatment with a product from the protection range **ProtectGuard®**.

## CHEMICAL NATURE

- Aqueous solution based on surfactants of vegetable origin.

## TECHNICAL DATA

Physical state at 20°C	: Liquid
Colour	: Blue
Odour	: None
pH	: 10.9 ± 0.5
Boiling point [°C]	: Not specified
Density	: 1.05 ± 0.01
Water solubility [vol/vol]	: Total
Flash point [°C]	: Not applicable

## CONSUMPTION

Figures stated are indicative only.

**5 to 8 m<sup>2</sup> / litre.**

## CLEANING OF EQUIPMENT

- Clean tools and equipment used with water immediately after use.

## STORAGE

- Store in a dry place at a temperature between 5°C and 30°C.
- Storage: 48 months from date of manufacture, in original packaging unopened.

## RECOMMENDATIONS

- Protect any metal surfaces (aluminium, zinc, tin, copper, light alloy etc.).
- For a perfect application, **Net'Guard® Ultra 4 in 1** must be used when the temperature of the substrates is between 5°C and 30°C.
- Do not apply in rainy or very hot weather.
- The ideal air temperature is between 5°C and 30°C.
- Do not mix with another product.
- Keep out of the reach of children.

## HEALTH / SAFETY

- **Respiratory protection:** No breathing apparatus is required under normal conditions of use provided there is adequate ventilation.
- **Protection of hands:** Wear latex gloves.
- **Skin protection:** Wear work clothes.
- **Protection of eyes:** If there is a significant risk of splashing, wear protective goggles.
- **If swallowed:** Do not induce vomiting. Contact a doctor or specialist.

**KEEP OUT OF REACH OF CHILDREN**

## TECHNICAL ASSISTANCE

### GUARD INDUSTRIE

7 Rue Gutenberg, 93100 MONTREUIL, FRANCE

Tel. +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail: [info@guardindustrie.com](mailto:info@guardindustrie.com) • [www.guardindustrie.com](http://www.guardindustrie.com)

**Important:** The content of this document is based on our experience of the product. Guard Industrie guarantees the quality of its products but expressly declines all liability in the event of failure by the user to respect the recommendations and conditions for using the said products, especially but not exclusively in the event of wrong application, application by unqualified personnel, use of products not compatible with the company's products or poor weather conditions. For more information, see safety data sheet.

**See the most recent update of our technical data sheet available on our website [www.guardindustrie.com](http://www.guardindustrie.com)**

Date updated: 20/01/2020